


**FAG****HCS7006-E-T-P4S-UL**

## High speed spindle bearing

High speed spindle bearing HCS70...-E, adjusted, in pairs or sets, contact angle  $\alpha = 25^\circ$ , with ceramic balls, lip seals on both sides, non-contact, restricted tolerances

## Technické informace



## Vaše aktuální varianta produktu

Contact angle	E	Contact angle 25°
Sealing	2RSD	non-contact sealed on both sides and greased "for life"
Outer shape	Standard	
Cage	T	Laminated fabric cage
Tolerance class	P4S	tolerance class P4S, FAG standard better than P4 to DIN 620
Arrangement bearing set	U	Single bearing
Preload	L	preload light

## Main Dimensions &amp; Performance Data

d	30 mm	Bore diameter
D	55 mm	Outside diameter
B	13 mm	Width
$C_r$	7.800 N	Basic dynamic load rating, radial
$C_{0r}$	3.850 N	Basic static load rating, radial
$C_{ur}$	310 N	Fatigue load limit, radial
$n_G$ Grease	43.000 1/min	Limiting speed for grease lubrication
$\approx m$	0,128 kg	Hmotnost



### Mounting dimensions

$d_a$	36 mm	Diameter shaft shoulder
$d_a$	h12	Diameter shaft shoulder clearance
$D_a$	49 mm	Shoulder diameter outer ring
$D_a$	H12	Shoulder diameter outer ring clearance
$r_{a \max}$	1 mm	Maximum recess radius
$r_{a1 \max}$	0,3 mm	Maximum recess radius
$a$	16,4 mm	Distance between the apexes of the pressure cones

### Dimensions

$r_{\min}$	1 mm	Minimum chamfer dimension
$r_{1 \min}$	1 mm	Minimum chamfer dimension
$\alpha$	25 °	Contact angle

### Temperature range

$T_{\min}$	-30 °C	Operating temperature min.
$T_{\max}$	80 °C	Operating temperature max.

### Additional information

$F_{VL}$	33 N	Preload force light
$F_{VM}$	98 N	Preload force medium
$F_{VH}$	197 N	Preload force heavy
$K_{aEL}$	94 N	Lift-off force light
$K_{aEM}$	287 N	Lift-off force medium
$K_{aEH}$	583 N	Lift-off force heavy
$c_{aL}$	60 N/μm	Axial rigidity light
$c_{aM}$	89 N/μm	Axial rigidity medium
$c_{aH}$	115 N/μm	Axial rigidity heavy



## Vlastnosti

---



Radiální zatížení



Axiální zatížení v jednom směru



Celoživotní mazání bez nutnosti údržby



Mazání (plastickým) mazivem



Utěsněné na obou stranách